



CLD-HW



CLD-ST

v4.2.0

# CLD-HW/ST



LIGHT DUTY

ABOVE CEILING

The Chameleon is specifically designed to be dropped into the ceiling above customer entry ways where a standard air curtain cannot be exposed. Like the CED, the Chameleon also has the least objectionable airflow.

## OPTIONS

### HEATING

Hot Water .....CLD-HW  
Steam .....CLD-ST  
Unheated .....pg 79  
Electric .....pg 79

### FILTER

½" Cleanable

### CUSTOM GRILLES

The white grille is standard with this model.  
Consult factory for custom color or metal.



## AT A GLANCE

Single Incremental Widths

3' to 12'

Max Installation Height

11'

Heavy Duty Motors

½ HP

### KEY DESIGN FEATURES

- White decorative intake grille with hinged access panel (consult factory for custom finishes)
- 1/2 HP ODP (Open Drip Proof) direct-drive dual-speed motor(s)
- High-efficiency discharge plenum with adjustable air foil vane (+/-20°)
- Coil made to AHRI Standard 410
- Hot water coil comprised of galvanized steel casing, 5/8" copper tube, aluminum fins, and same end supply/return connections
- Leak tested at 450 psi
- Custom coil selections available (consult factory)

### RECOMMENDED CONTROLS & ACCESSORIES

- Activation by 24V magnetic door switch
- Toggle disconnect switch
- SmartTouch controller
- Hot water or steam control valve with actuator
- Filter (washable)

