

► CLD-HW/ST | PERFORMANCE

CLD-HW/ST | Performance Table

MODEL	Nozzle Width (in.)	Max. FPM at Nozzle	Avg. FPM	CFM at Nozzle	Outlet Velocity Uniformity	Number of Motors	Motor HP	Hot Water		Steam		Weight (lbs)
								mbtu / Hour	Temp. Rise (°F)	mbtu / Hour	Temp. Rise (°F)	
CLD-1-36HW/ST	36	3000	1205	892	88%	1	1/2	33	34	32	32	196
CLD-1-48HW/ST	48	3000	1131	1108	89%	1	1/2	40	33	41	34	214
CLD-1-60HW/ST	60	3000	998	1227	79%	1	1/2	48	36	48	36	245
CLD-2-72HW/ST	72	3000	1205	1784	88%	2	1/2	66	34	65	33	392
CLD-2-84HW/ST	84	3000	1209	2080	90%	2	1/2	78	34	76	33	405
CLD-2-96HW/ST	96	3000	1131	2216	89%	2	1/2	86	35	83	35	420
CLD-3-108HW/ST	108	3000	1205	2676	88%	3	1/2	102	35	98	33	588
CLD-3-120HW/ST	120	3000	1176	2892	88%	3	1/2	112	35	107	34	605
CLD-3-132HW/ST	132	3000	1111	3011	79%	3	1/2	119	36	114	35	620
CLD-4-144HW/ST	144	3000	1205	3568	88%	4	1/2	137	35	131	34	784

- ! • For a unit over 12 feet long, consult factory.
• Performance values based off AMCA certified values of unheated CED air curtain.

CLD-HW/ST | Sound Levels

High Speed	53 dBA	Low Speed	51 dBA	Measured 10 ft. from unit in a free field based on a 1 motor unit
------------	--------	-----------	--------	---

CLD-HW/ST | Single Phase Motor Options

Voltages available	120	208/230	480	Note: 575v is transformed down to 120v
Amp draw per motor	2.5	1.4	0.7	



NOTE

When requesting a quote for a Hot Water/Steam heated air curtain, please provide:

- Specifics of water/steam entering and exiting the air curtain
- Location for water/steam supplies and returns (both on one side or one each side)