



TFD-HW



TFD-ST

► TFD-HW/ST | PERFORMANCE

TFD-HW/ST | Performance Table

Model	Nozzle Width (in.)	Max. FPM at Nozzle	Avg. Outlet Velocity FPM	CFM at Nozzle	Outlet Velocity Uniformity	Power Rating (kW)	Number of Motors	Motor HP	Sound Pressure (dBA)*	Sound Power [LWA] (dBA)	Hot Water		Steam		Weight (lbs.)
											mbtu/ Hour	Temp. Rise (°F)	mbtu/ Hour	Temp. Rise (°F)	
TFD-1-36HW/ST	36	4500	3108	2331	92.0%	1.2	1	1.5	73	87	85	34	90	36	165
TFD-1-48HW/ST	48	4500	3565	2565	94.0%	1.3	1	1.5	76	90	100	36	95	34	182
TFD-1-60HW/ST	60	4500	2146	2682	73.0%	1.3	1	1.5	69	82	103	36	101	35	212
TFD-2-72HW/ST	72	4500	3108	4662	92.0%	2.4	2	1.5	76	90	180	36	179	36	335
TFD-2-84HW/ST	84	4500	2798	4896	92.0%	2.6	2	1.5	79	93	184	35	187	35	346
TFD-2-96HW/ST	96	4500	2565	5130	94.0%	2.6	2	1.5	79	93	183	33	192	35	360
TFD-2-108HW/ST	108	4500	2332	5247	73.0%	2.6	2	1.5	79	93	196	35	205	36	382
TFD-3-108HW/ST	108	4500	3108	6993	92.0%	3.6	3	1.5	77	92	256	34	266	35	500
TFD-3-120HW/ST	120	4500	2891	7227	92.0%	3.7	3	1.5	80	95	274	35	268	34	516
TFD-3-132HW/ST	132	4500	2713	7461	92.0%	3.8	3	1.5	80	95	291	36	**		526
TFD-4-144HW/ST	144	4500	3108	9324	92.0%	4.8	4	1.5	79	93	346	34			665
TFD-4-156HW/ST	156	4500	2941	9558	92.0%	4.9	4	1.5	82	96	364	35			681
TFD-4-168HW/ST	168	4500	2798	9792	92.0%	5.0	4	1.5	82	96	381	36			692

*Calculation based on spherical free field at 5 ft.

**Contact factory for availability

! For a unit over 14 feet long, consult factory.
For Top Intake, consult factory.

TFD-HW/ST | Three Phase Motor Options

Voltages available	120	208	240	480	575
Amp draw per motor	NA	5.0	4.6	2.3	1.9

KEY DESIGN FEATURES

- Outer cabinet constructed of 18-gauge 304 stainless steel with #3 finish
- 1.5 HP TEAO (Totally Enclosed Air Over) direct-drive single-speed motor(s)
- High-efficiency discharge plenum with adjustable air foil vane (+/-20°)
- Top and bottom access panels for servicing and removal of motor-blower assembly
- NEMA 12 control panel
- Coil made to AHRI Standard 410
- Hot water coil comprised of galvanized steel casing, 5/8" copper tube, aluminum fins, and same end supply/return connections
- Leak tested at 450 psi
- Single length hot water coils up to 14 ft
- Single length steam coils up to 10 ft
- Custom coil selections available (consult factory)

RECOMMENDED CONTROLS

- Activation by 24V magnetic door switch
- Toggle disconnect switch
- Hand/Off/Auto selector switch
- Heat On/Off selector switch
- Digital thermostat
- Hot water or steam control valve with actuator